


910-824-1527 Don Lee equivalent? - Pyramat.



MATERIAL SPECIFICATION

P550



The composite turf reinforcement mat (C-TRM) shall be a machine-produced mat of 100% UV stabilized polypropylene fiber matrix incorporated into a permanent three-dimensional turf reinforcement matting.

The matrix shall be evenly distributed across the entire width of the matting and stitch bonded between the bottom and middle ultra heavy duty UV stabilized nettings with 0.50 x 0.50 inch (1.27 x 1.27 cm) openings and then covered by an ultra heavy duty UV stabilized nettings with 0.50 x 0.50 inch (1.27 x 1.27 cm) openings. The middle, dramatically corrugated (crimped) netting shall form prominent closely spaced ridges across the entire width of the mat. The three nettings shall be stitched together on 1.50 inch (3.81 cm) centers with UV stabilized polypropylene thread to form a permanent three-dimensional turf reinforcement matting.

The P550 shall meet requirements established by the Erosion Control Technology Council (ECTC) Specification and the U.S. Department of Transportation, Federal Highway Administration's (FHWA) Standard Specifications For Construction of Roads and Bridges on Federal Highway Projects, FP-03 2003 Section 713.18 as a Type 5A, B, and C Permanent Turf Reinforcement Mat.

Installation staple patterns shall be clearly marked on the turf reinforcement mattings with environmentally safe paint. All mats shall be manufactured with a colored thread stitched along both outer edges (approximately 2-5 inches [5-12.5 cm] from the edge) as an overlap guide for adjacent mats.

The composite turf reinforcement mat shall be the North American Green P550, or equivalent. The P550 permanent composite turf reinforcement mat shall have the following physical properties:

Material Content

|         |                                                                                                                                                                                                                                                                                                       |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Matrix  | 100% UV Stabilized Polypropylene Fibers<br>(0.50 lbs/yd <sup>2</sup> ) (0.27 kg/m <sup>2</sup> )                                                                                                                                                                                                      |
| Netting | Top and bottom- Ultra Heavy Duty UV Stabilized Polypropylene<br>(24 lb/1,000 ft <sup>2</sup> [11.7 kg/100 m <sup>2</sup> ] approximate weight)<br><br>Mid - Corrugated Ultra Heavy Duty UV Stabilized Polypropylene<br>(24 lb/1,000 ft <sup>2</sup> [11.7 kg/100 m <sup>2</sup> ] approximate weight) |
| Thread  | UV Stabilized Polypropylene                                                                                                                                                                                                                                                                           |

P550 is Available with the Following Physical Specifications Per Roll [English Units (Metric Units)]

|              |                                               |
|--------------|-----------------------------------------------|
| Width        | 6.50 ft (2.00 m)                              |
| Length       | 55.50 ft (16.90 m)                            |
| Weight ± 10% | 52 lbs (23.59 kg)                             |
| Area         | 40.00 yd <sup>2</sup> (33.40 m <sup>2</sup> ) |

Stitch Spacing for All Rolls = 1.50 inches (3.81 cm)